



SEE MORE. DO MORE.



ZEBRA[®] ZXP SERIES 1[™] CARD PRINTER SPECIFICATIONS



Specifications are provided for reference and are based on printer tests using Genuine Zebra[™] supplies. Results may vary in actual application settings or when using other-than-recommended Zebra supplies. Zebra recommends always qualifying any application with thorough testing.

Printing Specifications

- Dye-sublimation thermal transfer direct to card
- Full color or monochrome printing
- Single-sided printing
- 545 cph monochrome
- 130 cph YMCKO
- Edge-to-edge printing on standard CR-80 media

Standard Features

- Eco-Friendly Load-N-Go[™] drop-in ribbon ZXP Series 1 cartridges
- ZRaster[™] host-based image processing
- Auto calibration of ribbon
- USB 2.0 connectivity
- Microsoft[®] Certified Windows drivers
- Energy Star Certified
- Print Touch[™] NFC tag for online printer documentation access
- 100 card covered feeder (30 mil)
- 45 card capacity output hopper (30 mil)
- 16-character LCD operator control display
- 300 dpi (11.8 dots/mm) print resolution
- Two-year warranty on printer
- Two-year (unlimited passes) original printhead
- One-year hot swap (U.S. only)

Printing Throughput

Printing throughput (cards per hour) based on click to drop printing, average print coverage, with USB connectivity. Times may vary depending on the computer and other configurations.

Ribbon	Front	Back	Click to Drop (sec)		Throughput (cards/hr)	
			Printing	Printing & Mag Encoding	Printing	Printing & Mag Encoding
YMCKO	YMCKO	N/A	30	32	130	125
Mono	K	N/A	9	12	545	405

Encoding Options and Specifications

Magnetic stripe encoder – ISO 7811 (new and re-encoded; tracks 1,2, and 3; high and low coercivity; stripe down; 30 mil card only; factory install only)

Optional Features

- *CardSense[™] single-card feed mode
- ZebraCare[™] extended product warranty programs

Communications Interfaces

- USB V2.0 (cable included) - standard
- *Built-in 10/100 Ethernet - optional



SEE MORE. DO MORE.



Card Compatibility

NOTE: For optimum print quality and printer performance, use of Zebra genuine supplies is recommended.

- Card Thickness: 10-40 mil
- Card Size: CR-80, ISO 7810 format, Type ID-1, 2.12" (54 mm) x 3.38" (86 mm)
- Card Material: PVC and PVC composite
- Spot Color or monochrome print only on < 20 mil card thickness

Physical Specifications (standard model)

Parameter	
Height	9.3" (236 mm)
Width	7.9" (200 mm)
Depth	13.0" (330 mm)
Weight	11.6 lbs (5.3 kg)

**Field upgradeable options*

Electrical Specifications

- Auto-switching single-phase AC power
- Operating range: 90-132VAC and 190-264VAC RMS
- Frequency range: 47-63 Hz
- FCC Class A

Supplies Specifications

NOTE: The ZXP Series 1 printer is designed to work only with Zebra True Colours® ix Series™, ZXP Series 1 ribbons.

- Zebra ix Series intelligent technology automatically detects and authenticates ribbon
- Integrated cleaning roller included with each ribbon
- Media Starter Kit – 1 YMCKO ribbon, 100 30-mil PVC cards
- Cleaning Kit: 4 print engine cleaning cards and 4 feeder cleaning cards, 1000 images/card

True Colours ix Series ZXP Series 1 Ribbon Options

Ribbon Description	Eco Cartridge Image Count
YMCKO	100
Black Monochrome	1000
White Monochrome	500

Preventative Maintenance

- Zebra recommends cleaning the printer on a regular basis using standard Zebra cleaning supplies and parts. Consult the User's Guide for further details.

Environmental Specifications

- Operating temperature: 60° F to 86° F (15° C to 30° C)
- Storage temperature: 23° F to 131° F (-5° C to 55° C)
- Operating humidity: 20% to 65% non-condensing
- Storage humidity: 20% to 70% non-condensing
- Media storage:
 - Temperature: 41° F to 77° F (5° C to 30° C)
 - Humidity: 35% to 65% non-condensing
 - Do not store in direct sunlight

Drivers Supported

Microsoft Windows Certified Printer Drivers¹

Windows XP, Windows Vista®, Windows Server® 2003, Windows Server 2008, Windows 7 (32-bit and 64-bit compatible), Windows 8 (32-bit and 64-bit compatible)

Please see zebra.com for up to-date listing of supported systems.

⁽¹⁾Requires Firmware Release 2.00 or greater



Corporate Headquarters
+1 800 423 0442
inquiry4@zebra.com

Asia-Pacific Headquarters
+65 6858 0722
apacchannelmarketing@zebra.com

EMEA Headquarters
+44 (0)1628 556000
mseurope@zebra.com

Latin America Headquarters
+1 847 955 2283
inquiry4@zebra.com

Other Locations / USA: California, Georgia, Illinois, Rhode Island, Texas, Wisconsin **Europe:** France, Germany, Italy, the Netherlands, Poland, Spain, Sweden, Turkey, United Kingdom **Asia Pacific:** Australia, China, Hong Kong, India, Indonesia, Japan, Malaysia, Philippines, Singapore, South Korea, Taiwan, Thailand, Vietnam **Latin America:** Argentina, Brazil, Colombia, Florida (LA Headquarters in USA), Mexico **Africa/Middle East:** Dubai, South Africa

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

©2014 ZIH Corp. Zebra, the Zebra head graphic and True Colours are trademarks of ZIH Corp, registered in many jurisdictions worldwide. ZXP Series 1 and all product names and numbers are Zebra trademarks. All rights reserved. All other trademarks are the property of their respective owners.